

Index

Numerics

- +5 V signal
 - description (table), 2-3
 - power connections, 2-7
 - self-resetting protection circuit breaker, 2-7

A

- analog output signal connections
 - common questions, B-1
 - current output for NI 6704, 2-5
 - voltage output, 2-4
 - voltage output connections (figure), 2-4
- analog output specifications
 - current output, NI 6704 only, A-2
 - dynamic characteristics, A-2
 - stability, A-2
 - transfer characteristics, A-1
 - voltage output, A-1
- AO <0..15> (V) signals (table), 2-3
- AO <16..31> (I) signals (table), 2-3
- AO GND <0/16..15/31> signals (table), 2-3
- AO GND signal (table), 2-3
- AO *n* (I) connection as current output (figure), 2-5

B

- bus interface
 - circuitry, 3-2
 - specifications, A-3

C

- calibration
 - external calibration, 4-1
 - self-calibration, 4-1

- calibration certificate (NI resources), C-2
- CE compliance specifications, A-5
- common questions. *See* questions about NI 6703/6704

- conventions used in the manual, vii
- current output for NI 6704

- current output connections (figure), 2-5
- power-on state, 2-6
- signal connections, 2-5
- specifications, A-2

- custom cabling, 1-3

D

- D GND signal (table), 2-3
- Declaration of Conformity (NI resources), C-1
- diagnostic tools (NI resources), C-1
- digital I/O
 - example connections (figure), 2-6
 - hardware overview, 3-2
 - power-on state, 2-7
 - signal connections, 2-6
 - specifications, A-3
- documentation
 - conventions used in manual, vii
 - NI resources, C-1
 - related documentation, viii
- drivers (NI resources), C-1